

Yamaha Performance Bulletin

YPB#: PB_MAN_24XplodeCruise_VF250LA_4-13-10_PNT

Test Date: 4/13/10



Manitou® 24 X-plode Cruise

Length	24' 10"
Beam	8' 6"
Dry Weight (Boat Mfr. Published)	2,760 lbs.
Maximum HP	300 hp
Fuel Capacity	57 gals.
Pontoons (# / Diameter)	3 / SHP Package
Weight as Tested (Approximate)	3,922 lbs.

Manitou

PONTOON BOATS

Boat Manufactured By:

Manitou-Triton Industries • 7800 Northport Drive • Lansing, MI 48917
517-322-3822 • www.manitouboats.com

Yamaha VF250LA

Horsepower	250
Displacement	4.2 L
Weight (Catalog Published)	505 lbs.
Gear Ratio	1.75

Engine Mounting Height

Mounting Hole Position	#1
------------------------	----

Propeller

Series	Painted Stainless Steel Series
Diameter/Pitch	14-1/2 x 19
Yamaha Part #	61A-45974-00-98
Propeller Material	Painted Stainless Steel

Test Conditions

Number of People	2
Air / Water Temperature (Fahrenheit)	69° / 55°
Elevation	550'
Wind Velocity	5-10 MPH


Comments: Test weight includes 27 gallons of fuel, one battery, safety and test equipment. Fuel consumption data gathered with Yamaha Command Link® fuel management system. Zero-to-30 speed data gathered with aftermarket speedometer. Other speed data gathered with GPS receiver.

Notice to Consumer: The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.

Performance Data

RPM	MPH	GPH	MPG
1000	4.9	1.3	3.77
1500	7.1	2.2	3.23
2000	10.4	3.1	3.36
2500	14.6	4.3	3.40
3000	18.6	5.8	3.21
3500	22.6	7.8	2.90
4000	27.6	10.7	2.58
4500	34.0	14.0	2.43
5000	40.5	16.4	2.47
5500	47.2	21.2	2.23
5800	50.1	22.7	2.21

Seconds 0-30 MPH 5.10



Test performed and verified by Yamaha Application Engineers.

For More Information:

Yamaha Motor Corporation, U.S.A. • OEM Division, Marine Group
1270 Chastain Road NW • Kennesaw, GA 30144 • (800) 88-YAMAHA
For other Performance Bulletins, visit www.yamaha-motor.com.

© 2009 Yamaha Motor Corporation, U.S.A. All rights reserved.